



Lintex



Colour Range



Internal Translucent & Blockout Fabric

Roller Blind | Roman Shade | Panel Glide
3.0m width

Technical Information

	Translucent	Blockout
Composition:	100% Polyester with Clear Acrylic Coating	100% Polyester with Clear Acrylic Coating
Thickness:	0.50mm ± 10%	0.55mm ± 10%
Weight:	220 gsm ± 30%	410 gsm ± 30%
Cutting*:	Ultrasonic, Crush or Pressure Cut	
Colourfastness:	5 -6 Blue Scale (AS 2001.4.21)	
Fire Retardancy Information for NON FR Products^:	Suitable for all building classes except Class 9(b) entertainment venues. A summary of BCA requirements can be provided on request.	
	<small>^ Fabrics which are not FR treated, have been FR tested and have a Flammability result over 6 or fabrics which are not FR treated and have not undergone FR testing.</small>	

Range:	Item:	Width:	Roll Length:
	Translucent - 60040300090XXH	3000mm	30 metres
	Blockout - 60041290090XXH	3000mm	25 metres

Care & Cleaning Dusting with a feather duster is all that is required to keep your fabric looking good. For the removal of stains, dirt and grime, gently wipe fabric skins with a sponge soaked in lukewarm water. If marks are still visible, add a little detergent. Then dry gently with a clean cloth. Test in inconspicuous area before spot cleaning.

For more information contact us on:
hdarchitectural@hunterdouglas.com.au